

# CT23RT18/19 Double DIN Fitting Kit for Renault Vehicles



## IN THE KIT

- Double DIN Fascia Panel
- Frame Bracket

\*Note the fascia kit showcased throughout this instruction manual is the CT23RT19. The CT23RT18 comes with an additional double DIN cage, however, the installation process is similar.

# **APPLICATION**

Note: Application data is subject to change at any time

Renault Master 2020 >
Nissan NV400 2020 >
Opel/Vauxhall Movano 2020 >

Note: for vehicles without OEM touchscreen displays.

# FEATURES -

- Allows for the installation of a double DIN aftermarket stereo
- · Includes mounting brackets and fitting accessories
- Finished in matt black to match vehicle dashboard

#### DISCLAIMER

The information provided in this document is subject to change without notice due to manufacturer changes and/or improvements to the product/s. This instruction manual is based on documented data and research. The manufacturer of this product cannot be held responsible for any changes made to the vehicle by the manufacturer or damages that may occur through the installation of this product in accordance with the steps outlined herein.

# PRIOR TO INSTALLATION

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure that the correct tools are used during the installation to avoid damage to the vehicle or product. **Connects2 can not be held responsible for the installation of this product.** 

## INSTALLATION GUIDE

## DASH DISASSEMBLY



Begin by using a panel removal tool to pry away the main fascia trim that surrounds the main radio, this trim includes the top pocket.



With the trim out of the way, undo the 4x screws that surround the main head unit and remove it whilst disconnecting all of the wiring.

### **DASH ASSEMBLY**

3.



Using the 4x pre-existing screws from the main head unit, screw the frame bracket into place.

**CT23RT18:** if using the **CT23RT18,** install the head unit into the cage, using the brackets/accessories provided. This will then need to be slid into the dashboard once the frame bracket is mounted.

4.



With the radio fully connected, place the new fascia plate onto the dashboard to complete the installation.