



## FEATURES

- AGM (Absorbed Glass Mat) Technology
- Maintenance Free Design
- Non-Spillable, Leak Proof Construction
- Heavy Duty Pure Lead Grid Design
- Rugged ABS Reinforced Plastic Housing
- Shock and Vibration Resistant Construction
- Very Low Resistance for Ultra Fast Recovery
- M6 Ring Terminal Button Connectors

## APPLICATIONS



- Primary or Secondary Audio Power Source
- Marine/RV Starting or Supplemental Power
- Good for up to 1,500W Audio Power
- High Cranking Performance

## PHYSICAL SPECIFICATIONS


Approximate Weight	10.73kg
Approximate Dimensions	
Length	165mm
Width	176mm
Height	125mm
Total Height	125mm
Housing Material	Shock Resistant ABS
Terminal Type	M6 Insert

## PERFORMANCE SPECIFICATION

Nominal Voltage	12V
Nominal Capacity (20hr)	28Ah to 10.5V
Max Amps @ 77°F (25°C)	2,000A
HCA @ 77°F (25°C)	630A
MCA / CA @ 32°F (0°C)	530A
CCA @ 0°F (-18°C)	415A
Reserve Capacity (25A)	55 minutes to 10.5V



TERMINAL TYPE : M6



## TEMPERATURE SPECIFICATIONS

Nominal Operating Temp.	77°F (25°C)
Charge Temp. Range	14°F - 140°F (-10°C - 60°C)
Discharge Temp. Range	-4°F - 140°F (-20°C - 60°C)

Proper Charging is crucial to the life of your XS Power battery. It is very important that the temperature of the battery remains cool with respect to the charge voltage. The chart below will help ensure proper charge voltage with different ranges of ambient temperature.

## CHARGE VOLTAGE REFERENCE CHART

Temperature	32°F (0°C)	50°F (10°C)	68°F (20°C)	77°F (25°C)	86°F (30°C)	104°F (40°C)
Charge Voltage	15.20	15.00	14.80	14.70	14.50	14.30
Float Voltage	14.25	14.00	13.75	13.65	13.50	13.25