


strands®

-lighting division



Part No. 809505
WHITE




Part No. 809506
AMBER



Part No. 809507
RED



Part No. 809508
YELLOW



*Included: Mounting bracket for flat surfaces
Mounting bracket for curved surfaces
Mounting bracket with a 30° angle.

UNITY ROCK LIGHT *WORK LIGHT*



PART NO.	809505	809506	809507	809508
VOLTAGE	10-32V DC	10-32V DC	10-32V DC	10-32V DC
CONSUMPTION	7,8W	5,2W	5W	5,2W
THEORETICAL LUMEN	880 lm	880 lm	600 lm	600 lm
ACTUAL LUMEN	780 lm	340 lm	200 lm	460 lm
1 LUX @ M	17 m	-	-	-
COLOR TEMPERATURE	5700K	-	-	3000K
BEAM PATTERN	Flood	-	-	-
IP-CLASS	IP69K	IP69K	IP69K	IP69K
COLOR LENS	Clear	Clear	Clear	Clear
COLOR LED	White	Amber	Red	Yellow
CONNECTION	Cable	Cable	Cable	Cable
CABLE LENGTH	500 mm	500 mm	500 mm	500 mm
MATERIAL HOUSING	Aluminium	Aluminium	Aluminium	Aluminium
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
MATERIAL BRACKETS	Rubber	Rubber	Rubber	Rubber
LENGTH	74 mm	74 mm	74 mm	74 mm
DEPTH	14,3 mm	14,3 mm	14,3 mm	14,3 mm
HEIGHT	42 mm	42 mm	42 mm	42 mm
HEIGHT INCLUDING BRACKETS	46,6 mm	46,6 mm	46,6 mm	46,6 mm
CC	60 mm	60 mm	60 mm	60 mm
OPERATING TEMPERATURE	-30°C - +65°C	-30°C - +65°C	-30°C - +65°C	-30°C - +65°C
E-APPROVED	No	No	No	No
EMC-CERTIFICATE	ECE R10	ECE R10	ECE R10	ECE R10