


strands®


-lighting division




Part No. 850971
ROTATING BEACON XL




Part No. 850972
ROTATING BEACON XL




Part No. 850974
ROTATING BEACON



Part No. 850975
ROTATING BEACON



Part No. 850976
ROTATING BEACON BATTERY



BIG ENERGY ROTATING BEACON LED

LED



PART NO.	850971	850972	850974	850975	850976
VOLTAGE	12-24V DC	12-24V DC	12-24V DC	12-24V DC	5V DC
CONSUMPTION	30W	30W	20W	20W	15W
PATTERN	3	3	3	3	3
IP-CLASS	IP56	IP56	IP56	IP56	IP65
COLOR LENS	Clear	Amber	Amber	Amber	Amber
COLOR LED	Amber	Warm white	Warm white	Warm white	Warm white
CONNECTION	Cable	Cable	Cable	Pole mount	Type-C cable and cig plug
CABLE LENGTH	350 mm	350 mm	350 mm	-	1020 mm
TYPE OF BRACKET	-	-	-	-	Magnetic base
MATERIAL HOUSING	ABS	ABS	ABS	ABS	ABS
STRENGTH OF MAGNET	-	-	-	-	120 km/h
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
LENGTH	140 mm	140 mm	145 mm	131 mm	128 mm
DEPTH	140 mm	140 mm	145 mm	131 mm	128 mm
HEIGHT	190 mm	190 mm	121 mm	151 mm	140 mm
DIAMETER	140 mm	140 mm	145 mm	131 mm	128 mm
CC	110 mm	110 mm	114 mm	-	-
OPERATING TEMPERATURE	-20°C · +60°C	-20°C · +60°C	-20°C · +60°C	-20°C · +60°C	-20°C · +60°C
E-APPROVED	ECE R65	ECE R65	ECE R65	ECE R65	ECE R65
EMC-CERTIFICATE	ECE R10	ECE R10	ECE R10	ECE R10	ECE R10