

strands®

-lighting division



Part No. 900021
SMALL LEFT



Part No. 900022
SMALL RIGHT



Part No. 900023
MEDIUM LEFT




Part No. 900025
MEDIUM RIGHT





Part No. 900026
LONG LEFT





Part No. 900027
LONG RIGHT



Part No. 900021-900022



Part No. 900023/900025



Part No. 900026-900027

FREEDOM LIGHT GUIDE



PART NO.	900021	900022	900023	900025	900026	900027
VOLTAGE	12-24V DC	12-24V DC	12-24V DC	12-24V DC	12-24V DC	12-24V DC
CONSUMPTION	5,5W	5,5W	5,5W	5,5W	5,5W	5,5W
FUNCTION CONSUMPTION SPEC.	Front position: 2W Rear position: 2W Side marker: 1,5W	Front position: 2W Rear position: 2W Side marker: 1,5W	Front position: 2W Rear position: 2W Side marker: 1,5W	Front position: 2W Rear position: 2W Side marker: 1,5W	Front position: 2W Rear position: 2W Side marker: 1,5W	Front position: 2W Rear position: 2W Side marker: 1,5W
IP-CLASS	IP6K9K	IP6K9K	IP6K9K	IP6K9K	IP6K9K	IP6K9K
CONNECTION	Cable	Cable	Cable	Cable	Cable	Cable
CABLE LENGTH	400 mm	400 mm	400 mm	400 mm	400 mm	400 mm
MATERIAL HOUSING	Rubber	Rubber	Rubber	Rubber	Rubber	Rubber
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
COLOR LED	Amber, White, Red	Amber, White, Red	Amber, White, Red	Amber, White, Red	Amber, White, Red	Amber, White, Red
COLOR LENS	Dark	Dark	Dark	Dark	Dark	Dark
LENGTH	58 mm	58 mm	58 mm	58 mm	58 mm	58 mm
DEPTH	101,6 mm	101,6 mm	161,5 mm	161,5 mm	199 mm	199 mm
HEIGHT	100 mm	100 mm	112 mm	112 mm	145 mm	145 mm
HEIGHT INCLUDING BRACKET	101,6 mm	101,6 mm	161,5 mm	161,5 mm	199 mm	199 mm
CC	78,5 mm	78,5 mm	78,5 mm	78,5 mm	78,5 mm	78,5 mm
OPERATING TEMPERATURE	-40°C · +40°C	-40°C · +40°C	-40°C · +40°C	-40°C · +40°C	-40°C · +40°C	-40°C · +40°C
E-APPROVED	ECE R148	ECE R148	ECE R148	ECE R148	ECE R148	ECE R148
EMC-CERTIFICATES	ECE R10	ECE R10	ECE R10	ECE R10	ECE R10	ECE R10